Product Datasheet
CEA263E



CEA263E

RCCB 2P 63A 100mA A Class

Technical Features

Architecture	
Type of pole	1P+N
Number of poles	2
Electric current	
Rated current	63 A
Rated residual operating current Idn	100 mA
Breaking and opening capacity Idm	0.63 kA
Rated conditional short-circuit current Inc according to EN61008-1	6 kA
Rated current -25°C	63 A
Rated current at -20°C	63 A
Rated current -15°C	63 A
Rated current -10°C	63 A
Rated current -5°C	63 A
Rated current at 0°C	63 A
Rated current 5°C	63 A
Rated current 10°C	63 A
Rated current 15°C	63 A
Rated current at 20°C	63 A
Rated current 25°C	63 A
Rated current 30°C	63 A
Rated current 35°C	63 A
Rated current at 40°C	63 A
Rated current at 45°C	63 A
Rated current at 50°C	63 A
Rated current 55°C	63 A
Rated current 60°C	56 A
Rated current 65°C	49 A
Rated current 70°C	40 A
Installation, mounting	
Nominal tightening torque top terminal	2.80 - 2.80 Nm
Nominal tightening torque down terminal	2.80 - 2.80 Nm
Connectivity	
Type of connection	Screw terminal
Voltage	
Rated operational voltage Ue	230 - 230 V
Type voltage supply	AC
Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	4000 V
Max. operating voltage	253 V
Frequency	
Frequency	50 - 50 Hz
Capacity	
Number of modules	2
Compatibility	
Suitable for DIN Rail	Yes
Safety	
Residual current type	A
Ingress Protection (IP) class	IP20
Installation, mounting	
Type of top connection for modular devices	Screw terminal

Installation, mounting	
Type of bottom connection for modular devices	biconnect
Nominal tightening torque	2.80 - 2.80 Nm
Connection	
Cross-section of output with screws, for massive conductors	1 - 25 mm^2
Cross-section of output with screws, for flexible conductors	1 - 16 mm^2
Cross-section flexible conductor	16 mm^2
Cross-section rigid conductor	25 mm^2
Cross-section of input and output with screws, for flexible conductors	1 - 16 mm^2
Cross-section of input and output with screws, for massive conductors	1 - 25 mm^2
Power	
Total power loss under IN	8.70 W
Use conditions	
Max. altitude	2000 m
Operating temperature	-25 - 40 °C
Endurance	
Electric endurance in number of cycles	2000
Number of mechanical operations	4000
Connectivity	
Top connection alignment for modular devices	Aligned terminal
Down connection alignment for modular devices	Aligned terminal
Dimensions	
Height	83 mm
Width	35 mm
Depth	70 mm
Sustainability	
RoHS conform	Yes