Product Datasheet
LSN504



LSN504

Fuse carrier 3P+N 32A 690V L38 4M

Technical Features

Dimensions	
Height	76.50 mm
Width	70 mm
Depth	76.90 mm
Architecture	
Number of poles	4
Type of pole	3P+N
Electric current	
Rated current	32 A
Rated current of fuse cartridge	0.2 A 1 A 2 A 4 A 6 A 8 A 10 A 12 A 16 A 20 A 25 A 32 A
Capacity	
Number of modules	4
Use conditions	
Operating temperature	-40 - 70 °C
Installation, mounting	
Nominal tightening torque	2.20 - 2.20 Nm
Mounting on	DIN rail
Power	
Total power loss under IN	3.50 W
Voltage	
Rated insulation voltage Ui	1000 V
Rated impulse withstand voltage Uimp	6000 V
Type voltage supply	AC/DC
Overvoltage category according to IEC 60947-1	3
Safety	
Ingress Protection (IP) class	IP2X
Connection	
Cross-section of input and output with screws, for flexible conductors	1 - 16 mm^2
Cross-section of input and output with screws, for massive conductors	1 - 16 mm^2
Fuse	
Fuse size	10 x 38
Cover, door	
Interlockable	Yes
Sustainability	
REACh-SVHC free	Yes
RoHS conform	Yes