# Product Datasheet
VF112TD



VF112TD

**Small distributor,golf,flush,1row,12M,MS-terminal,N+PE,transparent door**

## Technical Features

| | |
|---|---|
| **Voltage** | |
| Nominal voltage | 400 - 400 V |
| **Installation, mounting** | |
| Suitable for outdoor usage | No |
| Mounting on | Flush mounting |
| **Electric current** | |
| Rated current IN | 63 A |
| **Equipment** | |
| Number of rails | 1 |
| Number of rows | 1 |
| Number of section in width | 1 |
| With lock | No |
| Has neutral terminal block | Yes |
| **Capacity** | |
| Number of modules | 12 |
| **Functions** | |
| With conduit inlets | Yes |
| **Dimensions** | |
| Height | 293 mm |
| Width | 352 mm |
| Depth | 97.50 mm |
| Built-in height | 257 mm |
| Built-in width | 318 mm |
| **Cover, door** | |
| Number of cabinet doors | 1 |
| **Dimensions** | |
| Built-in depth | 72 mm |
| **Cover, door** | |
| Number of locks | 0 |
| **Dimensions** | |
| Number of width units | 12 |
| **Cover, door** | |
| Door/cover is transparent | Yes |
| Cabinet door type | Single door |
| **Materials** | |
| Material | Plastic |
| RAL code | 9010 |
| Colour | Pure white |
| **Equipment** | |
| Has earthing terminal block | Yes |
| Has mounting plate | No |
| **Materials** | |
| Ultraviolet-resistant | No |
| **Safety** | |
| Protection class | Isolation class II |
| Impact resistance IK | IK07 |

| Safety | |
|---|---|
| Ingress Protection (IP) class | IP40 |
| Locking type | Snap on lock<br>Without lock |
| Glow wire test | 850 °C |
| Protection class with door | IP40 |

| Sustainability | |
|---|---|
| RoHS conform | Yes |