Product Datasheet
VF312TD



VF312TD1

Small distributor,golf,flush,3row,36M,MS-terminal,N+PE,transparent door

Technical Features

Voltage	
Nominal voltage	400 - 400 V
Installation, mounting	
Suitable for outdoor usage	No
Mounting on	Flush mounting
Electric current	
Rated current	63 A
Equipment	
Number of rails	3
Number of rows	3
Number of section in width	1
With lock	No
Has neutral terminal block	Yes
Capacity	
Number of modules	36
Functions	
With conduit inlets	Yes
Dimensions	
Height	543 mm
Width	352 mm
Depth	97.50 mm
Built-in height	507 mm
Built-in width	318 mm
Cover, door	
Number of cabinet doors	1
Dimensions	
Built-in depth	72 mm
Cover, door	
Number of locks	0
Dimensions	
Number of width units	12
Cover, door	
Door/cover is transparent	Yes
Cabinet door type	Single door
Materials	
Material	Plastic
RAL code	9010
Colour	Pure white
Equipment	
Has earthing terminal block	Yes
Has mounting plate	No
Materials	
Ultraviolet-resistant	No
Safety	
Protection class	Isolation class II
Impact resistance IK	IK07

Safety	
Ingress Protection (IP) class	IP40
Locking type	Snap on lock Without lock
Glow wire test	850 °C
Protection class with door	IP40

Sustainability	
RoHS conform	Yes