Product Datasheet
VS412TD



VS412TD1

Small distributor,golf,surface,4row,48M,MS-terminal,N+PE,transparent door

Technical Features

Voltage	
Nominal voltage	400 - 400 V
Installation, mounting	
Suitable for outdoor usage	No
Mounting on	Surface mounting
Electric current	
Rated current	63 A
Equipment	
Number of rails	4
Number of rows	4
Number of section in width	1
With lock	No
Has neutral terminal block	Yes
Capacity	
Number of modules	48
Functions	
With conduit inlets	Yes
Dimensions	
Height	647 mm
Width	282 mm
Depth	99 mm
Cover, door	
Number of cabinet doors	1
Number of locks	0
Dimensions	
Number of width units	12
Cover, door	
Door/cover is transparent	Yes
Cabinet door type	Single door
Materials	
Material	Plastic
RAL code	9010
Colour	Pure white
Equipment	
Has earthing terminal block	Yes
Has mounting plate	No
Materials	
Ultraviolet-resistant	No
Safety	
Protection class	Isolation class II
Impact resistance IK	IK07
Ingress Protection (IP) class	IP40
Locking type	Snap on lock Without lock
Glow wire test	650 °C
Protection class with door	IP40

Sustainability	
RoHS conform	Yes